

SUZUKI 2 strokes motors , true working machines, offer an unparalleled price/performance ratio and can withstand the most extreme operating conditions. These engines are perfect for equipping traditional fishing canoes. Suzuki's advanced technology provides fast starts, exceptional power, excellent fuel economy and smooth, quiet operation even at idle.

DT15AL



TECHNICAL CHARACTERISTICS	DT15AL
MOTOR	
Engine Type	In-line 2
Trim method (positions)	Manual
Reverse direction	Front/Neutral/Rear
Steering Control	Tiller Handle
Gear Ratio	1.92:1
Ignition System	SUZUKI PEI
Maximum Power (Kw)	11(15)
Start-up	Manual
Fuel	Fuel and Oil
Full throttle operating range (tr/min)	4800-5600
Bore x Stroke (mm)	59 x 52
Displacement (cc)	284
MORE	
Propeller Rotation	Clockwise
Alternator	12V/80W
DIMENSIONS	
Engine Oil Capacity (L)	25
Dry weight with propeller (kg)	39,5
Engine transom height (mm)	508
Oil capacity (L)	1
EQUIPMENTS	
REGULAR PROPELLER (3 blades)	DT15AL
	DT15AL
Material	ALUMINUM
Diameter	9 1/4

Always wear a helmet, eye protection and protective proper clothing.
CFAO encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.